



SP-5514 TOUCH POS SYSTEM

ADVANCED POS FUNCTIONALITY WITH STYLE



The Partner Tech SP-5514 touch screen terminal packs POS functionality into a modern, sleek design that compliments the décor of even the most stylish restaurants and retail settings. With five color options to choose from the SP-5514 compliments any store style and design.

POS that Works Almost Anywhere

The SP-5514 features a small footprint that can be used even where space is limited. The all-in-one offers options to add a full complement of peripherals including a card reader, fingerprint sensor, and NFC/RFID scanner, to keep counters uncluttered.

Not Just a Pretty Face

The SP-5514 has been designed to optimize workflows at the checkout. The 14-inch-wide, 16:9, PCT touchscreen makes it easy for your staff to use – even new employees can use intuitive touchscreen interfaces efficiently almost from day one.

Flexibile Interface

The SP-5514's design allows more flexibility to change the interface depending on your device requirements, allowing a variety of configurations using serial, USB, and Optional powered USB 12V*3 / 24V*1 for the retail market.

SPECIAL FEATURES

- Bezel-free 14" screen with projected capacitive touch (multi-touch)
- Dust-and spray-resistant front panel (IP65)
- Supports up to 8GB RAM
- Multiple I/O configurations available

OPTIONAL

- Available in Classic Black, Metallic Grey and Silver White
- Supports optional customer-facing display (2x 20 VFD, 7", 11.6" or 15")
- Optional peripherals: 3-track encryption-capable MSR, Bio reader, Chip Card reader, RFID/NFC

SP-5514

Item	SP-5514
CPU	Intel® Celeron™ J1900 (2.00GHz), quad core, 2MB L2 cache, fanless
LCD	Bezel-free 14" TFT-LCD, resolution 1366 x 768, brightness 220cd/m², LED back-light
Touch	Projected Capacitive Touch (multi-touch)
RAM	4GB DDR3L SO-DIMM
Storage	64G SSD or 2.5" SATA Hard Drive
LAN	1 x RJ-45 10/100/1000 BASE-T Gigabit Ethernet
I/O Interface	2 x COM (DC+0/5/12V: COM 1-2 BIOS selection) 3 x USB 2.0 1 x USB 3.0 1 x RJ-45 Ethernet 1 x RJ-11 Cash drawer control (for 2 cash drawers) 1 x VGA 1 x DC + 12V Out 1 x Mini PCI-e (internal) 1 x Audio connector
Optional Interface Expansion	1. RS-232 COM DB9 x 2 (0V/5V/12V selection by jumper) , 2. Or RS232 COM x 1 (DB9, 0V/5V/12V selection by JP) 3. Or Powered USB 12V x 3 & 24V x 1 PCBA (max 72W) 4. Or 1 x COM (0V/5V/12V selection by jumper) + USB 2.0 x 2
Speaker	1 x 3W speaker (internal)
Operating Systems	Windows 10
Power Supply	AC100~240V/DC+12V, 65W / 90W / 180W power adaptor
Dimensions	14.45in (W) x 9.92in (D) x 11.69in (H)
Environment	Temperature: Operating: 32°F ~ 104°F Storage: -4°F ~ 140°F Humidity: 15% ~ 80% 15% ~ 80%
Optional Peripherals	3-track MSR 2x20 line VF display Customer facing displays: 7", 11.6" or 15"
Color	Black

*Specification is subject to change without prior notice

